

Flowcrete Grasset

Product sheet

Product description

An alkaline, fast acting detergent designed for the removal of oil, grease and albumen deposits of animal and vegetable origin. The product contains substances which are authorized for the cleaning of food areas.

Uses

Can be used in cold and warm water and provides good corrosion protection (can be used on anodised aluminium). Suitable for alkali-resistant floors, walls and work surfaces in food processing areas e.g. canteens, butcher shops, slaughter houses, dairies, cheese dairies, bakeries, hospitals, hotels etc. Also suitable for foam producing machines.

Not suitable for use on alkali-sensitive surfaces such as linoleum, water dispersion varnishes etc.

Note: For professional use only. Not a consumer product according to 1999/44/EC Art.1.

Environment & Health

Flowcrete Grasset contains solvents. Follow the appropriate Occupational Health and Safety guidelines applicable to the location where the application is undertaken. For more information, please refer to the safety datasheets for the individual components.

pH

Concentrate has a pH of approximately 13. For the ready to use solution the pH is approx. 11.

Application

First step is to establish whether the material to be cleaned is alkali resistant - test a small inconspicuous spot before using the Grasset.

Routine cleaning (wiping, mechanical wet cleaning, surface cleaning)

Mix 50 - 200 ml in 8 litres of water (2 - 3 squirts). Consumption approx 1 ml/m².

Intensive cleaning

Mix 1 litre in 8 litres of water and scrub with a rotary floor machine. Consumption approx 40 ml/m².

Foam cleaning

Fill container with undiluted product. Depending on the degree of dirt, choose nozzle adjustment of 1:4 to 1:10. Foam the surface, leave for 10 minutes then rinse with clear water. Consumption approx 20 ml/m².

Removal of stubborn soil

Use undiluted Grasset from the spray bottle.

Work surfaces and kitchen furnishings which come into direct contact with food have to be wiped thoroughly with clean water. Warm water (40 to 60°C) accelerates the effectiveness of Grasset in case of stubborn build-up. For grease and albumen deposits, first use Grasset in the recommended solution with cold water, then scrub the floors with hot water coming from the tank of the rotary floor machine.

Coverage per square metre

Wiping / mechanical wet cleaning	0.5 – 1 ml
Surface cleaning	1 ml
Intensive cleaning	40 ml
Foam cleaning	20 ml

Storage

12 months in unopened pack. Storage temperature between 5°C and 40°C.
Protect from weather and moisture / contaminant ingress.

Packaging

The product is delivered in the following packs:-

Units	Carton of 6 x 1 litre bottles	10 litre bottles	200 litre barrel
-------	-------------------------------	------------------	------------------

Any suggested practices or installation specifications for the composite floor or wall system (as opposed to individual product performance specifications) included in this communication (or any other) from Flowcrete UK Ltd constitute potential options only and do not constitute nor replace professional advice in such regard. Flowcrete UK Ltd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.