

## Flowfast SNL Filler

### Product sheet

#### Product description

A blend of mineral fillers for use in Flowfast (blu) systems.

#### Uses

For mixing with Flowfast binder resins where an SL coating is required.

#### Environment & Health

Flowfast SNL Filler is inert and solvent free. Follow the appropriate Occupational Health and Safety guidelines applicable to the location where the application is undertaken. For more information, please refer to the safety datasheet.

#### Ratio of components

Use at up to 2:1 by weight of the selected Flowfast binder resin.

The Flowfast SNL Filler should be thoroughly stirred into the resin until a homogeneous lump-free slurry mix is obtained, mixing time 1 - 2 minutes.

Please consult specific Flowfast product datasheet for further details.

#### Colour

White.

#### Solids content

100 %

#### Density

Approx. 2.65 kg/litre.

#### Storage

12 months in unopened pack.

Storage temperature between 5°C and 25°C.

Protect from weather and moisture/contaminant ingress.

#### Packaging

The product is delivered in the following packs:

Unit            Flowfast SNL Filler

25 kg            (9.4 litres)

*Any suggested practices or installation specifications for the composite floor or wall system (as opposed to individual product performance specifications) included in this communication (or any other) from Flowcrete UK Ltd constitute potential options only and do not constitute nor replace professional advice in such regard. Flowcrete UK Ltd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.*